

419 Diamond Sof-Tred™



- Non-directional "Deck Plate" pattern.
- Exceptional worker comfort due to 12,7 mm thick newly formulated compound.
- Protective layer of exclusive Dyna-Shield™ extends service life by 50% compared to regular microcellular vinyl.
- Fire rating Class 2 according NFPA Safety Code 101.
- Available yellow borders along sides comply with OSHA code 1910-144.
- All 4 sides are bevelled and sealed to minimize tripping hazards.
- Free of toxic DOP and DMF.

419 Diamond Sof-Tred™

PRODUCT SPECIFICATIONS			
Designation	Industrial matting		
Type	Anti-fatigue		
Description	Non-directional "Deck Plate"		
Material	Microcellular vinyl		
Process	Foaming		
Category	Better		
Recommended use	Medium duty – dry areas		
Colours	Grey, Black, Black/Yellow		
Weight	4 kg/m ²		
Thickness	12.7 mm		
Standard sizes	60 cm x 91 cm 91 cm x 150 cm 60 cm x 18.3 m 91 cm x 18.3 m 122 cm x 18.3 m		
Custom sizes	60 cm, 91 cm and 122 cm per linear meter		
Special remarks	With Dyna-Shield™, a tough barrier which is 50% more resistant to wear.		
PRODUCT TESTING			
Tests	Norms	Results	
Compression deflection	U.S.		
	1.4 kg/cm ²		0,67 cm
	2.8 kg/cm ²		0,82 cm
Foam battery	ASTM D3574	40 lb/in ²	
Abrasion resistance	ASTM D3884-01		
	500 Cycles		0,83% weight loss
	1000 Cycles		2,20% weight loss
Static coefficient of friction	ASTM C1028-96	1,00	
Elongation	ASTM D412	147%	
Breaking load	ASTM D412	16.8 lb	
Graves tear strength	ASTM D 1004	12,1 lb	
Hardness	ASTM D2240-02	20 Shore A	
Anti-slip	DIN 51130 and BG-RULE BGR181		
FIRE TESTING			
	Critical radiant flux	ASTM E-648	
	Fire retardancy	DIN4102	
		EN 13501-1	
Flammability test	ASTM D2859	Pass	
ESD	ANSI ESD S7.1 50% Humidity		
Sustainability	<ul style="list-style-type: none"> • Recyclable material • Reach Compliant (Registration, Evaluation, Authorization and Restriction of Chemicals) 		